

High Temperature Tube Furnace GWL-GA



GWL Series 1200°C-1800°C High Temperature Tube Furnace

The equipment designed for pyrolysis, melting, analysis and production ceramics, metallurgy, electronics, machinery, chemical, glass, refractories, for develop new material, special materials, construction materials, the equipment is suitable for institutions of higher learning and laboratory of scientific research institute and industrial and mining enterprises.

The control panel equipped with the intelligent adjustment device, power control switch, main working/stop button, voltmeter, ammeter, Computer interface, Observe port / Air inlet port, for convenience to observe the furnace working status, the product using reliable integrated circuit, excellent working environment, anti-interference, the highest temperature of furnace shell temperature is less than 45 can greatly improve the working environment, micro computer program control, programmable setting temperature rise curve, Fully automatic temperature rise / cooling, Temperature control parameters and programs can be modified during operation, which is flexible, convenient and simple in operation.

Temperature Control Accuracy: $\pm 1^{\circ}\text{C}$, Temperature Constant Accuracy: $\pm 1^{\circ}\text{C}$. Fast Temperature rise rate, Maximum heating rate $\leq 30^{\circ}\text{C}/\text{min}$.

Furnace hearth materials made up by vacuum forming high purity alumina light materials (Will be changing due to the temperature required), High temperature for use, Less heat storage amount, Tolerance the extremely heating and cold, no crack, No dregs, Excellent thermal insulation performance (the energy saving effect is over 60% of the traditional furnace). Reasonable structure, Double layer furnace cover, Air cooling, Greatly shortening the experimental period.



Model	GWL-GA				
Working Temperature	1200℃	1400℃	1600℃	1700℃	1800℃
Maximum Temperature	1250℃	1450℃	1650℃	1750℃	1820℃
Heating Element	Silicon Carbide Rod		Silicon molybdenum rod		
Furnace Tube Diameter	30mm 50mm 60mm 80mm 90mm 100mm 110mm 150mm				
Length Of Heating Zone	150mm 250mm 300mm 400mm 500mm 600mm 700mm 1000mm 1200mm				
Temperature Rise Rate	Temperature Rise Rate Can Be Modify(1℃/h-30℃/min)				
Rated Voltage	380V				
Temperature Uniformity	±1℃				
Temperature Control Accuracy	±1℃				
Tube materials	1200℃: Stainless steel tube /Quartz tube / Corundum tube				
	1400℃-1800℃: Corundum tube				
Refractories	Import High Purity Alumina Fiber Board				
Standard Accessories	Heating Elements, Specification Certificate, Insulation Brick, Crucible Pliers, Of High Temperature Gloves. Special crucible for tube furnace, Seal rings				
Characteristic:					
Simplicity Operation; Less land occupation.					
1、Temperature accuracy: ±1℃ ; Constant temperature: ±1℃(Base on Heating zone size) 。					
2、Simplicity for operation, programmable, PID automatic modify, automatic temperature rise, automatic temperature retaining, automatic cooling, unattended operation					
3、Furnace tube uses 99 corundum tube or quartz tube 。					
4、Furnace surface temperature approach the indoor temperature.					
5、double layer loop protection. (over temperature protection, over pressure protection, over current protection, thermocouple protection, Power supply protection and so on)					
6、Importing refractory, excellent temperature retaining effect, high temperature resistance.					
7、Vacuum degree -0.1Mpa.					
8、More gas options (Oxygen、Nitrogen、Argon、hydrogen and so on)					
Furnace Tube Diameter And Length And Atmosphere Can Be Customized, More Details Please Contact Us					
Pressure, Tube quality, Flux accuracy Control, Remote Control Can Be Customized					